

Code: IPC-F22P

IP CAMERA **IPC-F22P** Wi-Fi BULLET 2C - 1080p 2.8 mm IMOU

The cameras of the IMOU series have been designed with special care to simplify the configuration and operation. In combination with the user friendly IMOU platform, the IMOU series devices allow anyone to create a simple and effective surveillance system.

Very easy operation via mobile devices (Android / iOS), allows the users for comfortable and remote operation, and also management of the camera. The used Wi-Fi module allows to remote communication with camera for max. distance up to 50 m. Camera is according to IP67 Index of Protection norm.

Attention! The IMOU series devices do not have a WEB interface. In order to obtain optimal performance of IMOU series cameras, it is recommended to use DAHUA Micro SD memory cards.



| | |
|---------------------------|--|
| Standard: | TCP/IP |
| Sensor: | 1/2.8 " Progressive Scan CMOS |
| Matrix size: | 2.1 Mpx |
| Resolution: | 1920 x 1080 - 1080p |
| Lens: | 2.8 mm |
| View angle: | 102 ° |
| Range of IR illumination: | 30 m |
| Audio: | <ul style="list-style-type: none"> • Microphone built-in, • Audio transmission via network |
| Image compression method: | H.265 / H.264 |
| Main stream frame rate: | 25 fps @ 1080p |
| Network protocols: | TCP, DHCP |
| ONVIF: | ✓ |



DATA SHEET

| | |
|--------------------------------|--|
| Network interface: | <ul style="list-style-type: none">• Ethernet : 100 Mbps• Wi-Fi IEEE 802.11 b/g/n - 2.4 GHz |
| WEB Server: | — |
| Mobile phones support: | Access by a cloud (P2P) <ul style="list-style-type: none">• Android: Free application IMOU• iOS (iPhone): Free application IMOU |
| Default admin user / password: | admin / - The administrator password should be set at the first start |
| Default IP address: | DHCP |
| Web browser access ports: | — |
| PC client access ports: | — |
| Mobile client access ports: | — |
| Port ONVIF: | — |
| RTSP URL: | — |
| Memory card slot: | Micro SD memory cards up to 256GB support (possible local recording) |
| Main features: | <ul style="list-style-type: none">• Wi-Fi Module - IEEE 802.11 b/g/n, Range : 50 m (open area)• Motion Detection• People detection• D-ZOOM - Digital Zoom : 16x |
| Power supply: | 12 V DC / 1 A (power adapter included) |
| Power consumption: | < 3.5 W |
| "Index of Protection": | IP67 |
| Weight: | 0.25 kg |
| Dimensions: | 148 x 74 x 74 mm |
| Supported languages: | — |
| Manufacturer / Brand: | DAHUA / IMOU |
| Guarantee: | 2 years |

